

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product name: **FUSOR 806HD HIGH DEFINITION SEALER**  
Product Use/Class: **SEALANT**

LORD Corporation  
111 LORD Drive  
Cary, NC 27511-7923

Telephone: 814 868-3180  
Non-Transportation Emergency: 814 763-2345  
Chemtrec 24 Hr Transportation Emergency No.  
800 424-9300 (Outside Continental U.S. 703 527-3887)

**EFFECTIVE DATE:** 01/21/2015

**2. HAZARDS IDENTIFICATION****GHS CLASSIFICATION:**

Acute toxicity Inhalation - Vapours Category 4 - 29.1% of the mixture consists of ingredient(s) of unknown toxicity.  
Carcinogenicity Category 2  
Specific target organ systemic toxicity (repeated exposure) Category 1 Lungs  
Aspiration hazard Category 1  
Hazardous to the aquatic environment - acute hazard Category 3  
Hazardous to the aquatic environment - chronic hazard Category 3

**GHS LABEL ELEMENTS:****Symbol(s)****Signal Word**

DANGER

**Hazard Statements**

Harmful if inhaled.  
Suspected of causing cancer.  
Causes damage to organs through prolonged or repeated exposure. (Lungs)  
May be fatal if swallowed and enters airways.  
Harmful to aquatic life.  
Harmful to aquatic life with long lasting effects.

**Precautionary Statements****Prevention**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Use personal protective equipment as required.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Avoid release to the environment.

**Response**

Call a POISON CENTER or doctor/physician if you feel unwell.  
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
Do NOT induce vomiting.

**Storage**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

**Other Hazards:**

**This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).**

**Acute:** Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea. May cause skin and eye irritation. May cause respiratory tract irritation. Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses. This product contains a residual amount of a chemical substance that may cause an allergic skin and/or respiratory reaction.

**Chronic:** Prolonged or repeated contact may result in dermatitis. Repeated or prolonged solvent overexposure may result in permanent central nervous system damage. IARC has designated titanium dioxide (TiO<sub>2</sub>) as Group 2B – possibly carcinogenic to humans in dust form. However, a number of long term animal studies and human epidemiology studies evaluating TiO<sub>2</sub> and workplace exposure show insufficient evidence for carcinogenic affects. EPA, NTP and OSHA do not designate TiO<sub>2</sub> as a carcinogen and ACGIH designates TiO<sub>2</sub> as A4 - not classifiable as a human carcinogen. TiO<sub>2</sub> is not present in this product as a dust and no airborne exposure is expected during application.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                      | CAS Number  | Weight % Less Than |
|------------------------------------|-------------|--------------------|
| High Boiling Petroleum distillates | PROPRIETARY | 25.0 %             |
| Titanium dioxide                   | 13463-67-7  | 5.0 %              |

### 4. FIRST AID MEASURES

**FIRST AID - EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

### 5. FIRE-FIGHTING MEASURES

**SUITABLE EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL:** Keep containers tightly closed. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

**SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are preferable.

## 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES:** Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid contact. Avoid breathing vapors. Use self-contained breathing equipment.

**ENVIRONMENTAL PRECAUTIONS:** Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:** Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Contain and remove with inert absorbent material and non-sparking tools.

## 7. HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation.

**STORAGE:** Do not store or use near heat, sparks, or open flame. Store only in well-ventilated areas. Do not puncture, drag, or slide container. Keep container closed when not in use.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### COMPONENT EXPOSURE LIMIT

| <u>Chemical Name</u>               | <u>ACGIH TLV-<br/>TWA</u> | <u>ACGIH TLV-<br/>STEL</u> | <u>OSHA PEL-<br/>TWA</u> | <u>OSHA PEL-<br/>CEILING</u> | <u>Skin</u> |
|------------------------------------|---------------------------|----------------------------|--------------------------|------------------------------|-------------|
| High Boiling Petroleum distillates | N.E.                      | N.E.                       | N.E.                     | N.E.                         | N.A.        |
| Titanium dioxide                   | 10 mg/m3                  | N.E.                       | 15 mg/m3                 | N.E.                         | N.A.        |

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

**Engineering controls:** Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area.

### PERSONAL PROTECTION MEASURES/EQUIPMENT:

**RESPIRATORY PROTECTION:** Use a NIOSH approved chemical/mechanical filter respirator designed to remove a combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

**SKIN PROTECTION:** Use neoprene, nitrile, or rubber gloves to prevent skin contact.

**EYE PROTECTION:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**OTHER PROTECTIVE EQUIPMENT:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

**HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

|                                               |                      |                               |                           |
|-----------------------------------------------|----------------------|-------------------------------|---------------------------|
| <b>ODOR:</b>                                  | Mild                 | <b>VAPOR PRESSURE:</b>        | N.D.                      |
| <b>APPEARANCE:</b>                            | Beige                | <b>VAPOR DENSITY:</b>         | Heavier than Air          |
| <b>PHYSICAL STATE:</b>                        | Paste                | <b>LOWER EXPLOSIVE LIMIT:</b> | 0.6 %(V)                  |
| <b>FLASH POINT:</b>                           | ≥ 201 °F, 93 °C      | <b>UPPER EXPLOSIVE LIMIT:</b> | 5 %(V)                    |
|                                               | Setaflash Closed Cup |                               |                           |
| <b>BOILING RANGE:</b>                         | N.A.                 | <b>EVAPORATION RATE:</b>      | Not Applicable            |
| <b>AUTOIGNITION TEMPERATURE:</b>              | N.D.                 | <b>DENSITY:</b>               | 1.25 g/cm3 - 10.40 lb/gal |
| <b>DECOMPOSITION TEMPERATURE:</b>             | N.D.                 | <b>VISCOSITY, DYNAMIC:</b>    | N.D.                      |
| <b>ODOR THRESHOLD:</b>                        | N.D.                 | <b>VISCOSITY, KINEMATIC:</b>  | N.D.                      |
| <b>SOLUBILITY IN H2O:</b>                     | Insoluble            | <b>VOLATILE BY WEIGHT:</b>    | 2.27 %                    |
| <b>pH:</b>                                    | N.A.                 | <b>VOLATILE BY VOLUME:</b>    | 3.04 %                    |
| <b>FREEZE POINT:</b>                          | N.D.                 | <b>VOC CALCULATED:</b>        | 0.24 lb/gal, 29 g/l       |
| <b>COEFFICIENT OF WATER/OIL DISTRIBUTION:</b> | N.D.                 |                               |                           |

**LEGEND:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

## 10. STABILITY AND REACTIVITY

**HAZARDOUS POLYMERIZATION:** Hazardous polymerization will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

**CONDITIONS TO AVOID:** High temperatures.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide

## 11. TOXICOLOGICAL INFORMATION

**EXPOSURE PATH:** Refer to section 2 of this SDS.

**SYMPTOMS:** Refer to section 2 of this SDS.

### TOXICITY MEASURES:

| <b>Chemical Name</b>               | <b>LD50/LC50</b>                                                                                          |
|------------------------------------|-----------------------------------------------------------------------------------------------------------|
| High Boiling Petroleum distillates | Oral LD50: Rat > 5,000 mg/kg<br>Dermal LD50: Rabbit > 2,000 mg/kg<br>Inhalation LC50: Rat > 5.2 mg/l /4 h |
| Titanium dioxide                   | Oral LD50: Rat > 10,000 mg/kg<br>GHS LC50 (vapour): rat 55 mg/l /                                         |

## 12. ECOLOGICAL INFORMATION

### ECOTOXICITY:

| <b>Chemical Name</b>               | <b>Ecotoxicity</b>                                                                                                                       |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| High Boiling Petroleum distillates | Fish: Pimephales promelas 45 mg/196 h flow-through<br>Lepomis macrochirus 2.2 mg/196 h Static<br>Oncorhynchus mykiss 2.4 mg/196 h Static |
| Titanium dioxide                   | N.D.                                                                                                                                     |

**PERSISTENCE AND DEGRADABILITY:** Not determined for this product.

**BIOACCUMULATIVE:** Not determined for this product.

**MOBILITY IN SOIL:** Not determined for this product.

**OTHER ADVERSE EFFECTS:** Not determined for this product.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality. Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

### 14. TRANSPORT INFORMATION

This product is NOT REGULATED for non-bulk US DOT Road, IATA Cargo or IMDG shipments. For the most accurate shipping information, refer to your transportation/compliance department regarding changes in package size, mode of shipment or other regulatory descriptors.

### 15. REGULATORY INFORMATION

#### U.S. FEDERAL REGULATIONS: AS FOLLOWS:

##### SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

NONE

#### TOXIC SUBSTANCES CONTROL ACT:

##### INVENTORY STATUS

The chemical substances in this product are on the TSCA Section 8 Inventory.

##### EXPORT NOTIFICATION

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

NONE

### 16. OTHER INFORMATION

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

**HMIS RATINGS - HEALTH: 2\* FLAMMABILITY: 1 PHYSICAL HAZARD: 0**

\* - Indicates a chronic hazard; see Section 2

**Revision:** New GHS SDS Format

**Effective Date:** 01/21/2015

### DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.