

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product name: **FUSOR 108B, 109B METAL BONDING ADH PT B**  
Product Use/Class: **ACRYLIC ADHESIVE, PART 2 OF 2**

LORD Corporation  
111 LORD Drive  
Cary, NC 27511-7923

Telephone: 814 868-3180  
Non-Transportation Emergency: 814 763-2345  
Chemtrec 24 Hr Transportation Emergency No.  
800 424-9300 (Outside Continental U.S. 703 527-3887)

**EFFECTIVE DATE:** 01/21/2015

**2. HAZARDS IDENTIFICATION****GHS CLASSIFICATION:**

Skin corrosion/irritation Category 2  
Serious eye damage/eye irritation Category 2A  
Skin sensitization Category 1  
Reproductive toxicity Category 1B  
Specific target organ systemic toxicity (single exposure) Category 1 Kidney, Nervous system  
Specific target organ systemic toxicity (repeated exposure) Category 2 Blood, brain, Hematopoietic System, Kidney  
Specific target organ systemic toxicity (repeated exposure) Category 2 Liver, Testes  
Specific target organ systemic toxicity (repeated exposure) Category 1 Upper respiratory system, Respiratory system  
Hazardous to the aquatic environment - acute hazard Category 1  
Hazardous to the aquatic environment - chronic hazard Category 2

**GHS LABEL ELEMENTS:****Symbol(s)****Signal Word**

DANGER

**Hazard Statements**

Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
May damage fertility or the unborn child.  
Causes damage to organs.(Kidney, Nervous system)  
May cause damage to organs through prolonged or repeated exposure in contact with skin.(Blood, brain, Hematopoietic System, Kidney)  
May cause damage to organs through prolonged or repeated exposure.(Liver, Testes)  
Causes damage to organs through prolonged or repeated exposure.(Upper respiratory system, Respiratory system)  
Very toxic to aquatic life.  
Toxic to aquatic life with long lasting effects.

**Precautionary Statements****Prevention**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Wear protective gloves/eye protection/face protection.  
Use personal protective equipment as required.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Contaminated work clothing should not be allowed out of the workplace.  
Avoid release to the environment.

**Response**

Get medical advice/attention if you feel unwell.  
IF exposed: Call a POISON CENTER or doctor/physician.  
Specific treatment (see supplemental first aid instructions on this label).  
IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/attention.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
Take off contaminated clothing and wash before reuse.  
Collect spillage.

**Storage**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

**Other Hazards:**

**This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).**

**Acute:** May cause respiratory tract irritation. Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

**Chronic:** Prolonged or repeated contact may result in dermatitis.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

| Chemical Name     | CAS Number  | Weight % Less Than |
|-------------------|-------------|--------------------|
| Epoxy resin       | PROPRIETARY | 30.0 %             |
| Benzoyl peroxide  | 94-36-0     | 5.0 %              |
| Dibutyl phthalate | 84-74-2     | 5.0 %              |

**4. FIRST AID MEASURES**

**FIRST AID - EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

**5. FIRE-FIGHTING MEASURES**

**SUITABLE EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL:** Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

**SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). If water is used, fog nozzles are preferable.

## 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES:** Avoid contact. Avoid breathing vapors. Use self-contained breathing equipment.

**ENVIRONMENTAL PRECAUTIONS:** Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:** Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Contain and remove with inert absorbent material.

## 7. HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation.

**STORAGE:** Store only in well-ventilated areas. Keep container closed when not in use.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### COMPONENT EXPOSURE LIMIT

| Chemical Name     | ACGIH TLV-TWA | ACGIH TLV-STEL | OSHA PEL-TWA | OSHA PEL-CEILING | Skin |
|-------------------|---------------|----------------|--------------|------------------|------|
| Epoxy resin       | N.E.          | N.E.           | N.E.         | N.E.             | N.A. |
| Benzoyl peroxide  | 5 mg/m3       | N.E.           | 5 mg/m3      | N.E.             | N.A. |
| Dibutyl phthalate | 5 mg/m3       | N.E.           | 5 mg/m3      | N.E.             | N.A. |

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

**Engineering controls:** Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

### PERSONAL PROTECTION MEASURES/EQUIPMENT:

**RESPIRATORY PROTECTION:** Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

**SKIN PROTECTION:** Use neoprene, nitrile, or rubber gloves to prevent skin contact.

**EYE PROTECTION:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**OTHER PROTECTIVE EQUIPMENT:** Remove and wash contaminated clothing before reuse.

**HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Typical values, not to be used for specification purposes.

|   |                      |                               |                                       |
|---|----------------------|-------------------------------|---------------------------------------|
| <b>ODOR:</b>                                  | Mild                 | <b>VAPOR PRESSURE:</b>        | N.D.                                  |
| <b>APPEARANCE:</b>                            | Black                | <b>VAPOR DENSITY:</b>         | Heavier than Air                      |
| <b>PHYSICAL STATE:</b>                        | Paste                | <b>LOWER EXPLOSIVE LIMIT:</b> | Not Applicable                        |
| <b>FLASH POINT:</b>                           | ≥ 201 °F, 93 °C      | <b>UPPER EXPLOSIVE LIMIT:</b> | Not Applicable                        |
|   | Setaflash Closed Cup |                               |                                       |
| <b>BOILING RANGE:</b>                         | N.A.                 | <b>EVAPORATION RATE:</b>      | Not Applicable                        |
| <b>AUTOIGNITION TEMPERATURE:</b>              | N.D.                 | <b>DENSITY:</b>               | 1.81 g/cm <sup>3</sup> - 15.02 lb/gal |
| <b>DECOMPOSITION TEMPERATURE:</b>             | N.D.                 | <b>VISCOSITY, DYNAMIC:</b>    | N.D.                                  |
| <b>ODOR THRESHOLD:</b>                        | N.D.                 | <b>VISCOSITY, KINEMATIC:</b>  | N.D.                                  |
| <b>SOLUBILITY IN H<sub>2</sub>O:</b>          | Insoluble            | <b>VOLATILE BY WEIGHT:</b>    | 0.33 %                                |
| <b>pH:</b>                                    | N.A.                 | <b>VOLATILE BY VOLUME:</b>    | 0.57 %                                |
| <b>FREEZE POINT:</b>                          | N.D.                 | <b>VOC CALCULATED:</b>        | 0 lb/gal, 0 g/10 g/l                  |
| <b>COEFFICIENT OF WATER/OIL DISTRIBUTION:</b> | N.D.                 |                               |                                       |

**LEGEND:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

**10. STABILITY AND REACTIVITY**

**HAZARDOUS POLYMERIZATION:** Hazardous polymerization will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

**CONDITIONS TO AVOID:** High temperatures.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide

**11. TOXICOLOGICAL INFORMATION**

**EXPOSURE PATH:** Refer to section 2 of this SDS.

**SYMPTOMS:** Refer to section 2 of this SDS.

**TOXICITY MEASURES:**

| Chemical Name     | LD50/LC50   |
|-------------------|---|
| Epoxy resin       | Oral LD50: Rat 11,400 mg/kg   |
| Benzoyl peroxide  | Oral LD50: Rat 6,400 mg/kg  |
| Dibutyl phthalate | Oral LD50: Rat 6,300 mg/kg<br>Dermal LD50: Rabbit >20 mL/kg<br>Inhalation LC50: Rat > 15.68 mg/l /4 h |

**12. ECOLOGICAL INFORMATION**

**ECOTOXICITY:**

| Chemical Name | Ecotoxicity |
|---------------|-------------|
| Epoxy resin   | N.D.        |

|                   |   |
|-------------------|---|
| Benzoyl peroxide  | N.D.  |
| Dibutyl phthalate | <u>Fish:</u> Pimephales promelas 0.71 - 1.2 mg/196 h flow-through<br>Pimephales promelas 0.31 - 5.45 mg/196 h Static<br>Oncorhynchus mykiss > 1.24 mg/196 h flow-through<br>Oncorhynchus mykiss 1.24 - 5.3 mg/196 h Static<br>Lepomis macrochirus 1.38 - 1.74 mg/196 h flow-through<br>Lepomis macrochirus 0.42 - 1.28 mg/196 h Static<br><u>Invertebrates:</u> Daphnia magna 2.99 mg/148 h Static<br>Daphnia magna 3.4 mg/148 h<br><u>Plants:</u> Desmodemus subspicatus 1.2 mg/172 h<br>Pseudokirchneriella subcapitata 0.4 mg/196 h Static |

**PERSISTENCE AND DEGRADABILITY:** Not determined for this product.

**BIOACCUMULATIVE:** Not determined for this product.

**MOBILITY IN SOIL:** Not determined for this product.

**OTHER ADVERSE EFFECTS:** Not determined for this product.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality. Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

### 14. TRANSPORT INFORMATION

**US DOT Road**

**DOT Proper Shipping Name:** Environmentally hazardous substances, liquid, n.o.s.  
**DOT Hazard Class:** 9  
**SECONDARY HAZARD:** None  
**DOT UN/NA Number:** 3082  
**Packing Group:** III  
**Emergency Response Guide Number:** 171

For US DOT non-bulk road shipments this material may be classified as NOT REGULATED. For the most accurate shipping information, refer to your transportation/compliance department regarding changes in package size, mode of shipment or other regulatory descriptors.

**IATA Cargo**

**PROPER SHIPPING NAME:** Environmentally hazardous substance, liquid, n.o.s.  
**DOT Hazard Class:** 9  
**HAZARD CLASS:** None  
**UN-NUMBER:** 3082  
**PACKING GROUP:** III  
**EMS:** 9L

**IMDG**

**PROPER SHIPPING NAME:** Environmentally hazardous substance, liquid, n.o.s.  
**DOT Hazard Class:** 9  
**HAZARD CLASS:** None  
**UN-NUMBER:** 3082  
**PACKING GROUP:** III  
**EMS:** F-A

The listed transportation classification applies to IATA Cargo and IMDG non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors for your country or particular locality. For the most accurate shipping information, refer to your transportation/compliance department.

### 15. REGULATORY INFORMATION

**U.S. FEDERAL REGULATIONS: AS FOLLOWS:**

**SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

| <u>Chemical Name</u> | <u>CAS Number</u> | <u>Weight % Less Than</u> |
|----------------------|-------------------|---------------------------|
| Benzoyl peroxide     | 94-36-0           | 5.0 %                     |
| Dibutyl phthalate    | 84-74-2           | 5.0 %                     |

**TOXIC SUBSTANCES CONTROL ACT:**

**INVENTORY STATUS**

The chemical substances in this product are on the TSCA Section 8 Inventory.

**EXPORT NOTIFICATION**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

NONE

|                              |
|------------------------------|
| <b>16. OTHER INFORMATION</b> |
|------------------------------|

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

**HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 1 PHYSICAL HAZARD: 1**

\* - Indicates a chronic hazard; see Section 2

**Revision:** New GHS SDS Format

**Effective Date:** 01/21/2015

|                   |
|-------------------|
| <b>DISCLAIMER</b> |
|-------------------|

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.